

TOP ALTITUDE: ASSIGNED BY ATC

PHOENIX DEP CON
124.9 353.8
ATIS ★
133.5 270 275
CINC DEL
135.05
GND CON
128.25 275.8
GATEWAY TOWER ★
120.6 289.4

TAKEOFF MINIMUMS
Rwys 12L/C/R: Standard with a minimum climb of 250' /NM to 3100.
Rwys 30L/C/R: Standard.

NOTE:
1. Turboprops and turboprops only.
2. Aircraft requesting FL220 and below must file BLYTHE Transition.
3. Turboprops landing LAX, file WLVRN Transition.
4. Aircraft landing other than LAX and turboprops landing at LAX: Requesting FL240 and above, file HRRBR Transition.
5. Aircraft departing KGEU and KGYR ATC assigned only.

DEPARTURE ROUTE DESCRIPTION
TAKEOFF RUNWAYS 12L/C/R: Climb on heading 124° or as assigned by ATC, thence. . . .
TAKEOFF RUNWAYS 30L/C/R: Climb on heading 304° or as assigned by ATC, thence. . . .
... for RADAR vectors to KEENS, then on track 259° to IZZO, then on (transition).
Maintain ATC assigned altitude, expect filed altitude 3 minutes after departure.

BLYTHE TRANSITION (IZZO8.BLH)
HRRBR TRANSITION (IZZO8.HRRBR)
WLVRN TRANSITION (IZZO8.WLVRN)

NOTE: Chart not to scale.