

LOC I-CRG <u>111.7</u>	APP CRS 321°	Rwy Idg TDZE Apt Elev	4008 41 41
----------------------------------	------------------------	-----------------------------	---------------------------------------


ILS or LOC RWY 32
JACKSONVILLE EXEC AT CRAIG (CRG)

T Night landing: Rwy 5 NA. DME or radar required. Helicopter
A visibility reduction below 1 SM NA. When local altimeter setting not received, use Jacksonville Intl altimeter setting: increase DA to 273 feet; increase all MDAs 40 feet and Circling visibility Cat C ¼ SM. For inop MALS, increase S-LOC 32 Cts C/D visibility to 1¼ mile. For inop MALS, when using Jacksonville Intl altimeter setting, increase S-LOC 32 Cts C/D visibility to 1¾ mile.



MISSED APPROACH: Climb to 700 then climbing right turn to 1900 on heading 180° and on CRG VORTAC R-139 to JEVAG/CRG VORTAC 11.8 DME/RADAR and hold.

ATIS 125.4	JACKSONVILLE APP CON 124.9 308.4	CRAIG TOWER ★ 132.1 (CTAF) 0 269.525	GND CON 121.8	CLNC DEL 118.35	UNICOM 122.95
---------------	-------------------------------------	---	------------------	--------------------	------------------



ELEV	41	TDZE	41
------	----	------	----

Diagram illustrating the FAF 5.7 NM from MRL Rwy 5-23. The diagram shows a runway layout with MRL Rwy 5-23 (4008 X 100) and HIRL Rwy 14-32 (4004 X 100). A TWR is located at 122. A 321° 5.7 NM distance is indicated from the FAF to the runway. Various navigation aids and symbols are shown, including a star for the TWR, a circle with a cross for the FAF, and a circle with a dot for the runway.

MRL Rwy 5-23

HIRL Rwy 14-32

REIL Rwy 14 and 23

FAF to MAP 5.7 NM					
Knots	60	90	120	150	180
Min:Sec	5:42	3:48	2:51	2:17	1:54

700 ↑	1900 hdg 180°	CRG R-139	JEVAG CRG 11.8	ADERR CRG 5.8 RADAR	JEVAG CRG 11.8 RADAR	One Minute Holding Pattern
CATEGORY	A	B	C	D		
S-ILS 32	241-1		200 (200-1)			
S-LOC 32	480-1		439 (500-1)			
CIRCLING	500-1 459 (500-1)	600-1 559 (600-1)	620-1½ 579 (600-1½)	800-2½ 759 (800-2½)		