

WAAS CH 65907 W36A	APP CRS 360°	Rwy Idg TDZE Apt Elev	9320 321 341
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 36L

MEMPHIS INTL(MEM)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 48°C (118°F). Simultaneous approach authorized. DME/DME RNP-0.3 NA. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations.



ALSF-2

ⓐ

MISSED APPROACH: Climb to 5000 direct SUNRE and on track 302° to KALIE and hold, continue climb-in-hold to 5000.

MEMPHIS APP CON		MEMPHIS TOWER		GND CON	
119.1	291.6 (176°-355°)	(Rwy 9-27)	118.3 257.8	(Rwy 9-27)	121.0 379.2
125.8	338.3 (356°-175°)	(Rwys 18C-36C, 18L-36R)	119.7 257.8	(Rwys 18C-36C, 18L-36R)	121.9 379.2
		(Rwy 18R-36L)	128.425 257.8	(Rwy 18R-36L)	121.65 379.2

D-ATIS 127.75	CINC DEL 125.2	CPDLC
-------------------------	--------------------------	-------



5000	SUNRE	tr 302°	KALIE	FREA Z	4 NM Holding Pattern
*LNAV only.					
*1.2 NM to RW36L					
VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 73).					
1.2 3.8 NM 3.1 NM 4.2 NM					
CATEGORY	A	B	C	D	
LPV DA	673/40 352 (400-¾)				
LNAV/VNAV DA	760/50 439 (500-1)				
LNAV MDA	780/24	459 (500-½)	780/40	780/50	
			459 (500-¾)	459 (500-1)	
CIRCLING	940-1	599 (600-1)	940-1½	1020-2¼	
			599 (600-1½)	679 (700-2¼)	