

APP CRS 180°	Rwy Idg TDZE Apt Elev	9320 295 341
------------------------	-----------------------------	---


RNAV (RNP) Y RWY 18R
MEMPHIS INTL (MEM)

T For uncompensated Baro-VNAV systems, procedure NA below -9°C (16°F) or above 48°C (118°F). Simultaneous approach authorized. GPS required. Use of FD or AP required during simultaneous operations. For inop ALS, increase RNP 0.19* all Cats visibility to RVR 6000 and RNP 0.30 all Cats visibility to 1 3/4 SM.	MALSR  MISSED APPROACH: Climb to 5000 on track 180° to JAGUR and on track 223° to JEPOB and hold. *Missed approach requires minimum climb of 425 feet per NM to 1000.
--	---

MEMPHIS APP CON			MEMPHIS TOWER			GND CON		
119.1	291.6	(176°-355°)	(Rwy 9-27)	118.3	257.8	(Rwy 9-27)	121.0	379.2
			(Rwys 18C-36C, 18L-36R)	119.7	257.8	(Rwys 18C-36C, 18L-36R)	121.9	379.2
125.8	338.3	(356°-175°)	(Rwy 18R-36L)	128.425	257.8	(Rwy 18R-36L)	121.65	379.2

D-ATIS 127.75	(IF)	CLNC DEL 125.2	CPDLC
-------------------------	------	--------------------------	-------

RADAR REQUIRED



5000 ↑	tr 180°	JAGUR ✦	tr 223°	JEPOB △
-----------	------------	------------	------------	------------

CATEGORY	A	B	C	D
RNP 0.19 DA*		645/40	350 (400-¾)	
RNP 0.30 DA		771/60	476 (500-1¼)	

AUTHORIZATION REQUIRED

MEMPHIS, TENNESSEE
Orig-E 29MAR18

35°03'N-89°59'W

MEMPHIS INTL (MEM)
RNAV (RNP) Y RWY 18R

SE-1, 21 MAR 2024 to 18 APR 2024