


APP CRS	Rwy Idg	8000
350°	TDZE	834
	Apt Elev	842

RNAV (RNP) Y RWY 35

MINNEAPOLIS-ST PAUL INTL/WOLD-CHAMBERLAIN (MSP)

▼ For uncompensated Baro-VNAV systems, procedure NA below -19°C (-2°F) or above 54°C (130°F). For inop ALSF, increase RNP 0.30 all Cats visibility to 1½ miles. GPS required.	ALSF-2	MISSED APPROACH: Climb to 1300 then climbing left turn to 3000 direct LYDIA and hold.
---	---	--

D-ATIS	MINNEAPOLIS APP CON	MINNEAPOLIS TOWER	GND CON	CLNC DEL
ARR 135.35 239.275	118.725 335.65 (Rwy 35)	123.675 273.55 (17-35)	N 121.8 348.6	133.2
DEP 120.8	119.3 335.65 (12L-30R, 4-22, 17)	123.95 273.55 (12L-30R)	S 121.9 348.6	
	126.95 335.65 (12R-30L)	126.7 273.55 (12R-30L, 4-22)	W 127.925 348.6	



ELEV 842	D	TDZE 834
HIRL all Rwys		
REIL Rwy 17		
TDZ/CL Rwys 12L, 12R, 30L, and 35		

1300 ↑	3000 ↖	LYDIA △	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).	
See planview for multiple IF locations.			LORAH 3000	ROZEE 4000
RW35			350°	GP 3.00° TCH 55
6.6 NM			3.1 NM	
CATEGORY	A	B	C	D
RNP 0.11 DA	1213/40		379 (400-¾)	
RNP 0.16 DA	1291/60		457 (500-1¼)	
RNP 0.30 DA	1345-1¼		511 (600-1¼)	

AUTHORIZATION REQUIRED

NC-1, 21 MAR 2024 to 18 APR 2024

NC-1, 21 MAR 2024 to 18 APR 2024