

LOC I-FSD 109.9	APP CRS 030°	Rwy Idg TDZE Apt Elev	8999 1424 1430
---------------------------	------------------------	-----------------------------	---

ILS or LOC RWY 3

JOE FOSS FLD (FSD)

T

A

ASR

-31°C

MALSR

MISSED APPROACH: Climb to 3400 then left turn direct FSD VORTAC and hold.

ATIS 126.6	SIoux FALLS APP CON * 125.8 306.2	SIoux FALLS TOWER * 118.3 (CTAF) 0 257.8	GND CON 121.9 348.6	UNICOM 122.95
----------------------	---	--	-------------------------------	-------------------------

ADF or RADAR REQUIRED

SIoux FALLS
115.0 FSD
Chan 97

LOCALIZER 109.9
I-FSD

ALTERNATE MISSED APCH FIX

ROKKY
245 FS
RADAR

MSA FS 25 NM
4500
3500

One Minute Holding Pattern		FS LOM RADAR	3400	FSD	ELEV 1430	TDZE 1424
					REIL Rwy 15 and 33	
GS 300° TCH 54		MAREY INT	*LOC only		HIRL Rwy 3-21 and 15-33	
3400 ← 210° 030° →		*1940			MIRL Rwy 9-27	
4.3 NM		1.4 NM			TDZ/CL Rwy 21	
CATEGORY	A	B	C	D		
S-ILS 3	1674/24 250 (300-½)					
S-LOC 3	1940/24	516 (600-½)	1940/55	516 (600-1)		
CIRCLING	1960-1 530 (600-1)	1980-1 550 (600-1)	2060-1¾ 630 (700-1¾)	2200-2½ 770 (800-2½)		
MAREY FIX MINIMUMS (DUAL VOR RECEIVERS REQUIRED)						
S-LOC 3	1800/24	376 (400-½)	1800/35	376 (400-¾)		
CIRCLING	1960-1 530 (600-1)	1980-1 550 (600-1)	2060-1¾ 630 (700-1¾)	2200-2½ 770 (800-2½)		
					FAF to MAP 5.7 NM	
					Knots	60 90 120 150 180
					Min:Sec	5:42 3:48 2:51 2:17 1:54

SIoux FALLS, SOUTH DAKOTA

Amdt 27G 18JUN20

43°35'N-96°45'W

JOE FOSS FLD (FSD)

ILS or LOC RWY 3