

APP CRS
087°

Rwy Idg **10000**
TDZE **91**
Apt Elev **96**

RNAV (RNP) Y RWY 9

GEORGE BUSH INTCNL/HOUSTON (IAH)

▼

For uncompensated Baro-VNAV systems, procedure NA below -3°C (27°F) or above 54°C (130°F). GPS required. For inop MALSR, increase all Cats visibility to 1½ mile. Simultaneous approach authorized. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MALSR

MISSED APPROACH: Climb to 580 then climbing right turn to 3000 direct JEBBOX and hold.

D-ATIS 124.05	HOUSTON APP CON 120.05 379.1 EAST 124.35 316.15 WEST	HOUSTON TOWER 135.15 290.2	GND CON 118.575	CLNC DEL 128.1	CPDLC
-------------------------	--	--------------------------------------	---------------------------	--------------------------	-------

RNAV (RNP) Y RWY 9 approach chart details:

- IAF URANG: 5000, 087° (5)
- CHILT: 4000, 087° (4.2)
- MEDIC 210K: 4000, 087° (3.8)
- DOHNN: 3000, 087° (3.9)
- SAYNO: 2000, 087° (4.7)
- HHOOG: 3000, 087° (4.5)
- TEXXN: 4900, 087° (3.5)
- HOWLN: 6000, 210K (RF REQD), 267° (3.7)
- JEBBOX: MISSED APCH FIX, 4 NM radius
- MSA RWY 09 25 NM: 3100

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).

580 3000 JEBBOX

SAYNO 3000 087° 2000 HYWAY 2000

GP 3.00° TCH 50

4.7 NM 5.8 NM

RWY 09

CATEGORY A B C D

RNP 0.30 DA 516/49 425 (500-1)

AUTHORIZATION REQUIRED

ELEV 96 TDZE 91

9000 X 150 26R 26L 9402 X 150 26R 26L 10000 X 150 27 33L 33R

087°

TDZ/CL Rwy's 8R, 8L, 15R, 26R, 26L, 27 and 33L

HIRL all Rwy's

HOUSTON, TEXAS

GEORGE BUSH INTCNL/HOUSTON (IAH)

Orig-B 13SEP18

29°59'N-95°20'W

RNAV (RNP) Y RWY 9