


LOC/DME I-IPJ 111.15 Chan 48 (Y)	APP CRS 233°	Rwy Idg TDZE 872 Apt Elev 878	ILS Z or LOC Z RWY 23 ILNCLNTN-LINCOLN COUNTY RGNL (IPJ)
---	------------------------	---	---

⚠ When local altimeter setting not received, use Charlotte altimeter setting: increase DA to 1212 feet and visibility 1/8 SM; increase all MDAs 80 feet and visibility S-LOC 23 Cats C/D 1/8 SM and Circling Cats C/D 1/4 SM and GATEQ Fix Minimums Cats C/D 1/4 SM. VDP NA when using Charlotte altimeter setting. Rwy 23 helicopter visibility reduction below 3/4 SM NA.

MISSED APPROACH: Climb to 1600 then climbing right turn to 3100 on heading 043° and BZM VOR/DME R-143 to JIVOM INT/I-IPJ 13.4 DME/RADAR and hold.

AWOS-3 119.675	CHARLOTTE APP CON 134.75 257.2	CLNC DEL (GCO) 124.9	UNICOM 123.05 (CTAF) 0
--------------------------	--	--------------------------------	----------------------------------



ELEV 878	TDZE 872	1600	3100	BZM R-143	JIVOM INT	CISBU INT I-IPJ 6 RADAR	JIVOM INT HPJ 13.4 RADAR	One Minute Holding Pattern
233°		*1540 When using Charlotte altimeter setting.						
*LOC only.		*I-IPJ 2.2 HPJ 1						
5700 X 100		2500						
0.3% UP		2500						
5700 X 100		2500						
REIL Rws 5 and 23 MRL Rwy 5-23		2500						
FAF to MAP 5 NM		2500						
Knots 60 90 120 150 180		2500						
Min:Sec 5:00 3:20 2:30 2:00 1:40		2500						
ILNCLNTN, NORTH CAROLINA		ILNCLNTN-LINCOLN COUNTY RGNL (IPJ)						
Orig-D 14JUL22		35°29'N-81°10'W						
		ILS Z or LOC Z RWY 23						