

RADAR INSTRUMENT APPROACH MINIMUMS

ATLANTIC CITY, NJ
ATLANTIC CITY INTL (ACY)
RADAR-1 124.6 327.125

Amdt 16A, 11AUG22 (22223) (FAA)

ELEV 75

ASR	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
	13		AB	480/24	405	(500-½)	CDE	480/40	405	(500-¾)
	4		AB	480-1	412	(500-1)	CDE	480-1½	412	(500-1½)
	31		AB	480/55	416	(500-1¼)	CDE	480/60	416	(500-1¼)
	22		AB	600-1	532	(600-1)	CDE	600-1½	532	(600-1½)
CIRCLING	ALL RWY		A	600-1	525	(600-1)	B	600-1	525	(600-1)
			C	620-1½	545	(600-1½)	D	640-2	565	(600-2)
			E	760-2½	685	(700-2½)				

For inoperative MALSR, increase ASR S-13 CAT C/D/E visibility to RVR 6000.
Rwy 4 helicopter visibility reduction below ¾ SM not authorized.

MC GUIRE FLD, (JOINT BASE MC GUIRE DIX LAKEHURST) (KWRI),
NJ (Amdt 1, 18032 USAF)
RADAR (E) - 119.05 120.0 269.025

ELEV 141

PAR	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
	18'	3.0°/51/950	ABCDE	322-¾	200	(200-¾)
	36	3.0°/46/950	ABCDE	429-1	300	(300-1)

No-NOTAM MP: 0400-1100Z++ Mon-Fri, (by NOTAM if required).
PAR apch avbl 1200-0200Z++ Mon-Fri.
*Rwy 18, VGSI and PAR glidepaths not coincident.

21 MAR 2024 to 18 APR 2024

21 MAR 2024 to 18 APR 2024

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

WHEELER-SACK AAF (KGTB), Fort Drum, NY RADAR-1 Amdt 1A RADAR-2 Amdt 1
15JUN23 (23166) (USA) ELEV 690
RADAR¹- 124.875 307.125 

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
RADAR-1						
PAR ^{2 3}	3	3.0°/54/1038	ABCDE	885-½	200	(200-½)
	21	3.0°/58/1106	ABCDE	877-½	200	(200-½)
RADAR-2						
ASR	21 ⁴		ABCDE	1100-¾	423	(500-¾)
	3 ⁵		AB	1240-½	555	(600-½)
			C	1240-1⅙	555	(600-1⅙)
			D	1240-1¼	555	(600-1¼)
			E	1240-1½	555	(600-1½)
CIR ⁶	All Rwy		AB	1240-1	550	(600-1)
			C	1240-1½	550	(600-1½)
			D	1380-2¼	690	(700-2¼)
			E	1640-3	950	(1000-3)

¹Opr 1500-0400Z++ Mon-Fri exc federal hol.
²When ALS inop, increase CAT ABCDE vis to ¾ mile.
³VGSI and PAR glide path not coincident.
⁴When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1¼ miles.
⁵When ALS inop, increase CAT AB vis to 1 mile, CAT C vis to 1⅙ miles, CAT D vis to 1¼ miles, CAT E vis to 2 miles.
⁶Circling NA E of Rwy 21 and 33. Circling NA for CAT E to Rwy 8-26 and Rwy 15-33. Circling NA for CAT B, C, and D to Rwy 8.

21 MAR 2024 to 18 APR 2024

21 MAR 2024 to 18 APR 2024

RADAR INSTRUMENT APPROACH MINIMUMS