RNAV (RNP) Z RWY 24

BIRMINGHAM-SHUTTLESWORTH INTL (BHM)

APP CRS	Rwy Idg	TDZE	Apt Elev
239°	10801	641	650

RNP AR APCH. RF required.

For uncompensated Baro-VNAV systems, procedure NA below -8°C or above 54°C. For inop ALS, increase RNP 0.15 all Cats visibility to 1⅜ and increase RNP 0.30 all Cats visibility to 1¾ SM.

MALSR

MISSED APPROACH: Climb to 3000 on track 238° to YACUR then, right turn to WADEG, then on track 067° to VLKNN and hold.

ATIS	BIRMINGHAM APP CON	BIRMINGHAM TOWER	GND CON	CLNC DEL
119.4 270.1	123.8 256.8	119.9 317.725	121.7 348.6	125.675 305.2



CATEGORY	A	B	C	D
RNP 0.15 DA	1149-1	508 (500-1)		
RNP 0.30 DA	1243-1⅜	602 (600-1⅜)		

REIL Rwys 18 and 36
TDZ/CL Rwy 6
HIRL Rwy 6-24
MIRL Rwy 18-36

AUTHORIZATION REQUIRED

SE-4, 18 APR 2024 to 16 MAY 2024