

APP CRS	Rwy Idg	10000
003°	TDZE	707
	Apt Elev	748

RNAV (RNP) Z RWY 36C

CHARLOTTE/DOUGLAS INTL (CLT)



RNP AR APCH - GPS.

Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. For uncompensated Baro-VNAV systems, procedure NA below -8°C or above 54°C. For inop ALS, increase RNP 0.30 visibility all Cats to 1½ SM.

ALSF-2

MISSED APPROACH: Climb to 3000 on track 003° to TOMME and hold.

D-ATIS	CHARLOTTE APP CON	CHARLOTTE TOWER	GND CON	CLNC DEL
ARR 121.15	(001°-119°) 128.32	(Rwys 18L-36R) 118.1 257.8	121.8 348.6 (WEST)	127.15
DEP 132.1	(120°-295°) 120.05	(Rwy 18C-36C) 126.4 257.8	121.9 348.6 (EAST)	348.6
	(296°-360°) 134.75	(Rwy 18R-36L) 133.35 257.8		
	(180°-359°) 257.2			
	(360°-179°) 307.8			



3000	↑ tr 003°	TOMME	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 72).					SOLMN	
			GLASI	NIVSE	MARJO	DENNE	HUNEX	KRISL	003° 8000
			2500	3000	4000	5000	6000	7000	
			5.4 NM	1.6 NM	3.2 NM	3.2 NM	3.2 NM	3.2 NM	GP 3.05° TCH 57
CATEGORY			A		B		C		D
RNP 0.11 DA					1134/40 427 (400-¾)				
RNP 0.30 DA					1180/50 473 (500-1)				
AUTHORIZATION REQUIRED									