RNAV (RNP) Z RWY 6R

CLEVELAND-HOPKINS INTL (CLE)

APP CRS	Rwy Idg	8029
058°	TDZE	777
	Apt Elev	799

RNP AR APCH.

For uncompensated Baro-VNAV systems, procedure NA below -18°C (0°F) or above 46°C (114°F).
For inop ALS, increase RNP 0.15 all Cats visibility to RVR 5500.

MALSR

MISSED APPROACH: Climb to 3000 direct MOMBE and on track 099° to NEIIL and hold.
*Missed approach requires minimum climb of 270 feet per NM to 1400.

D-ATIS	CLEVELAND APP CON	CLEVELAND TOWER	GND CON	CLNC DEL	CPDLC
ARR 127.85 DEP 132.375	126.55 346.325	124.5 273.45	121.7 273.45	125.05 273.45	



See planview for multiple IF locations.

3000	MOMBE	tr 099°	NEIIL



CATEGORY	A	B	C	D
RNP 0.15 DA*		1127/30	350 (400-⅝)	
RNP 0.30 DA		1229/45	452 (500-⅞)	

AUTHORIZATION REQUIRED

ELEV 799 D TDZE 777



REIL Rwy 10
TDZ/CL Rwy 6L, 6R, 24L, and 24R
HIRL Rwys 6L-24R, 6R-24L and 10-28

EC-2, 18 APR 2024 to 16 MAY 2024
EC-2, 18 APR 2024 to 16 MAY 2024