WAAS CH 69618 W17A	APP CRS 172°	Rwy Idg 13500 TDZE 6187 Apt Elev 6187

RNAV (GPS) Y RWY 17L

CITY OF COLORADO SPRINGS MUNI (COS)

RNP APCH - GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 44°C. For inop MALSR, increase LNAV Cat C/D visibility to 2½ SM.

MALSR

MISSED APPROACH: Climb to 9000 direct CEGIX and on track 100° to DRAKE and hold.

ATIS	SPRINGS APP CON	SPRINGS TOWER	GND CON	CLNC DEL
125.0 254.3	124.0 257.875	119.9 360.6	121.7 348.6	134.45 363.125





CATEGORY	A	B	C	D
LPV DA	6387/18		200 (200-½)	
LNAV/VNAV DA	6602/45		415 (500-⅞)	
LNAV MDA	7000/24 813 (900-½)	7000/40 813 (900-¾)	7000-1⅞ 813 (900-1⅞)	
C CIRCLING	7000-1¼ 813 (900-1¼)		7040-2½ 853 (900-2½)	7260-3 1073 (1100-3)



MIRL Rwy 13-31
HIRL Rwys 17R-35L and 17L-35R
REIL Rwys 13, 17R, 31, and 35R
TDZ/CL Rwys 17L and 35R

SW-1, 18 APR 2024 to 16 MAY 2024
SW-1, 18 APR 2024 to 16 MAY 2024