RNAV (GPS) RWY 5

DES MOINES INTL (DSM)

WAAS	APP CRS	Rwy Idg	9004
CH 69202	053°	TDZE	931
W05A		Apt Elev	958

RNP APCH - GPS.

T A For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4500. *RVR 1800 authorized with use of FD or AP or HUD to DA (NA when using Ankeny Rgnl altimeter setting).

MALSR (A5)

MISSED APPROACH: Climb to 3100 direct IOWAA and hold.

ATIS	DES MOINES APP CON	DES MOINES TOWER	GND CON	CLNC DEL
119.55	123.9 307.15	118.3 257.8	121.9 348.6	134.15 317.55





CATEGORY	A	B	C	D
LPV DA*	1131/24	200 (200-½)		
LNAV/VNAV DA	1247/24	316 (300-½)		
LNAV MDA	1320/24	389 (400-½)	1320/35	389 (400-⅝)
C CIRCLING	1420-1	462 (500-1)	1600-1¾ 642 (700-1¾)	1760-2½ 802 (900-2½)

ELEV 958 D TDZE 931



REIL Rwys 5 and 23
TDZ/CL Rwy 31
HIRL Rwys 13-31 and 5-23

NC-3, 18 APR 2024 to 16 MAY 2024
NC-3, 18 APR 2024 to 16 MAY 2024