

VOR OLK
110.4

APP CRS
114°

Rwy Idg **2623**
TDZE **836**
Apt Elev **836**

VOR RWY 13
SMITH FLD (SMD)

▼

▲ NA

☒ -22°C

Rwy 13 helicopter visibility reduction below 1 SM NA. Procedure NA at night. When local altimeter setting not received, use Fort Wayne Intl altimeter setting and increase all MDA 40 feet and S-13 Cat C visibility 1/8 SM.

MISSED APPROACH: Climb to 1900 then climbing left turn to 2700 direct OLK VOR and hold.

AWOS-3 124.55	FORT WAYNE APP CON 127.2 284.6	UNICOM 122.8 (CTAF) 0
-------------------------	--	---------------------------------

One Minute Holding Pattern

OLK VOR

2700 ← 294°
114° →

1900

2700

OLK

HIWAY INT RADAR

2600

3.00° TCH 40

11.2 NM

5.4 NM

CATEGORY	A	B	C	D
S-13	1360-1 524 (600-1)	1360-1½ 524 (600-1½)	1940-3 1104 (1200-3)	NA
☒ CIRCLING	1400-1 564 (600-1)			NA

MIRL Rwy 5-23 and 13-31 0

ELEV	836	TDZE	836		
Knots	60	90	120	150	180
Min:Sec	5:24	3:36	2:42	2:10	1:48

FORT WAYNE, INDIANA
Amdt 11 25MAY17

41°09'N-85°09'W

SMITH FLD (SMD)
VOR RWY 13