ILS or LOC RWY 16

FORT WORTH MEACHAM INTL (FTW)

LOC I-FTW	APP CRS	Rwy Idg	7502
109.9	164°	TDZE	710
Chan 36		Apt Elev	710

*RVR 1800 authorized with the use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 1300 then climbing left turn to 2500 direct FT LOM and hold, continue climb-in-hold to 2500.

ATIS	REGIONAL APP CON	MEACHAM TOWER	GND CON	CLNC DEL
120.7	(North) 118.1 306.95 (South) 135.975 379.9	118.3 257.8	121.9	124.65

ADF REQUIRED

BOWIE
117.15 UKW
Chan 118 (Y)

4000
144°
(44.6)

344°
209°
029°
164°
344°

LOM/IAF
MUFIN
365 FT
I-FTW 5.3

MAVERICK
113.1 TTT
Chan 78

R-269

1049
990
913
1022
1049
1198
1743

LOCALIZER 109.9
I-FTW
Chan 36

MSA FT 25 NM
180°
2200
2800
270°
3600
360°

MUFIN LOM/INT
I-FTW 5.3

Remain within 10 NM

344°
164°
2400
1992
2000

GS 3.00°
TCH 57

1300	2500	FT

I-FTW 3
I-FTW 1.5

2.3 NM — 1.5 NM

ELEV 710 D TDZE 710

164°
9
17
35
34
4005 X 75
0.5% UP
7502 X 150
TWR
751
HIRL Rwy 16-34
MIRL Rwy 17-35

CATEGORY	A	B	C	D
S- ILS 16*	910/24	200 (200-½)		
S- LOC 16	1240/24	530 (600-½)	1240/50 530 (600-1)	1240/60 530 (600-1¼)
CIRCLING	1260-1 550 (600-1)	1280-1 570 (600-1)	1340-1¾ 630 (700-1¾)	1500-2½ 790 (800-2½)

FAF to MAP 3.8 NM

Knots	60	90	120	150	180
Min:Sec	3:48	2:32	1:54	1:31	1:16

SC-2, 18 APR 2024 to 16 MAY 2024
SC-2, 18 APR 2024 to 16 MAY 2024