


LOC/DME I-VQX 110.75 Chan 44(Y)	APP CRS 274°	Rwy ldg 7500 TDZE 667 Apt Elev 680
---	------------------------	---

ILS or LOC RWY 28L

CHICAGO O'HARE INTL (ORD)

Aircraft not GPS equipped - RADAR required for procedure entry. DME or RADAR required.	ALSF-2	MISSED APPROACH: Climb to 1200 then climbing left turn to 4000 direct CGT VORTAC and hold.
From VOGLR: RNAV 1-GPS required.		
Simultaneous approach authorized.		

D-ATIS 135.4 282.225	CHICAGO APP CON 119.0 292.125	O'HARE TOWER 133.0 348.0	GND CON (TWR NORTH) 124.125 (TWR SOUTH) 118.05 (ALL TWRs) 226.675	(TWR CENTER) I-VQX (OBND) 121.75 I-VQX (IBND) 121.9	CLNC DEL 121.6	CPDLC
--	--	------------------------------------	--	---	--------------------------	-------



ELEV 680 TDZE 667		1200 4000 CGT		*LOC only.	
CATEGORY		A		B	
S-ILS 28L		867/18 200 (200-1/2)		867/18 200 (200-1/2)	
S-LOC 28L		1240/24 573 (600-1/2)		1240-1/4 573 (600-1/4)	
FAF to MAP 4.7 NM		ALKYL FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)		ALKYL FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)	
Knots 60 90 120 150 180		S-LOC 28L		1060/24 393 (400-1/2)	
Min:Sec 4:42 3:08 2:21 1:53 1:34				1060/35 393 (400-5/8)	