RNAV (GPS) RWY 9C

CHICAGO O'HARE INTL (ORD)

WAAS	APP CRS	Rwy ldg	11245
CH 58143	093°	TDZE	673
W09D		Apt Elev	680

RNP APCH.

Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. For inop ALS, increase LNAV/VNAV all cats visibility to RVR 4500 and LNAV Cat C/D to 1⅜ SM.

ALSF-2

MISSED APPROACH: Climb to 1200 then climbing left turn to 4000 direct DEERE and hold.

D-ATIS	CHICAGO APP CON	O'HARE TOWER	GND CON	(TWR CENTER)	CLNC DEL	CPDLC
135.4 282.225	119.0 292.125	121.15 348.0	124.125 (TWR NORTH) 118.05 (TWR SOUTH) 226.675 (ALL TWRS)	121.75 (OBND) 121.9 (IBND)	121.6	







VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 72).

1200 | 4000 | DEERE

*LNAV only.



CATEGORY	A	B	C	D
LPV DA	873/18	200 (200-½)		
LNAV/VNAV DA	976/24	303 (300-½)		
LNAV MDA	1140/24	467 (500-½)	1140/50	467 (500-1)

ELEV 680 D TDZE 673



HIRL all Rwys
TDZ/CL all Rwys except 4L

EC-3, 18 APR 2024 to 16 MAY 2024
EC-3, 18 APR 2024 to 16 MAY 2024