CHICAGO, ILLINOIS

AL-166 (FAA)

RNAV (GPS) PRM RWY 28C (CLOSE PARALLEL)

CHICAGO O'HARE INTL (ORD)

WAAS	APP CRS	Rwy ldg 10800
CH 53639	273°	TDZE 651
W28B		Apt Elev 680

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Use of FD or AP providing RNAV track guidance required during simultaneous operations. Simultaneous approach authorized. Dual VHF comm required. See additional requirements on AAUP.

ALSF-2

MISSED APPROACH: Climb to 1100 then climbing left turn to 4000 direct DPA VOR/DME and hold.

D-ATIS	CHICAGO APP CON	O'HARE TOWER	GND CON	(TWR CENTER)	CLNC DEL	CPDLC
135.4 282.225	119.0 292.125	120.75 348.0 PRM 119.625	124.125 (TWR NORTH) 118.05 (TWR SOUTH) 226.675 (ALL TWRS)	121.75 (OBND) 121.9 (IBND)	121.6	

RADAR REQUIRED



2325





ELEV 680 D TDZE 651



HIRL all Rwys
TDZ/CL all Rwys except 4L



CATEGORY		A	B	C	D
LPV	DA	851/18	200 (200-½)		
LNAV/VNAV	DA	1094/50	443 (500-1)		