

APP CRS	Rwy Idg	9000
271°	TDZE	3852
	Apt Elev	3877

RNAV (RNP) Z RWY 27

HELENA RGNL (HLN)

RNP AR APCH - GPS.

▼

▲

❄

Inop table does not apply to RNP 0.30 DA. For uncompensated Baro-VNAV systems, procedure NA below -28°C or above 54°C. For inop ALS, increase RNP 0.13 DA* visibility all Cats to ¾ SM, RNP 0.30 DA* visibility all Cats to 1 ¾ SM.

MALSR

AS

MISSED APPROACH:

Climb to 12000 on the RNAV missed approach route to PIXXI and hold, continue climb-in-hold to 12000.

*Missed approach requires minimum climb of 280 feet per NM to 7800.

#Missed approach requires minimum climb of 375 feet per NM to 6300.

ATIS 120.4	HELENA APP CON* 119.5 229.4	HELENA TOWER* 118.3 (CTAF) 0 257.8	GND CON 121.9	UNICOM 122.95
---------------	--------------------------------	---------------------------------------	------------------	------------------

Procedure NA for arrivals at HLN VORTAC on V113 northeast bound.

Procedure NA for arrivals at SUZZY on V343 westbound.

Procedure NA for arrival on HIA VOR/DME airway radials 353 CW 078.

MISSED APCH FIX

MSA RW 27 25 NM

REIL Rlys 9, 17, and 35

MIRL Rlys 5-23 and 17-35

HIRL Rwy 9-27

ELEV 3877	D	TDZE 3852								
12000	KISTY	tr 271°	KELTY	tr 265°	PIXXI	tr 275°	JEXUT	tr 271°	GOKME	tr 271°
See planview for multiple IF locations.										
RW27										
GP 3.00° TCH 55										
CATEGORY										
RNP 0.13 DA*										
RNP 0.20 DA#										
RNP 0.30 DA#										
RNP 0.30 DA										
AUTHORIZATION REQUIRED										

HELENA, MONTANA

Amdt 2 25JAN24

46°36'N-111°59'W

HELENA RGNL (HLN)

RNAV (RNP) Z RWY 27