

APP CRS 320°	Rwy Idg	7278
	TDZE	793
	Apt Elev	796

RNAV (RNP) Z RWY 32

INDIANAPOLIS INTL (IND)

▼

For uncompensated Baro-VNAV systems, procedure NA below -18°C (2°F) or above 54°C (130°F). GPS required.

MALSR

MISSED APPROACH: Climb to 3000 on track 320° to KEADY and hold.

D-ATIS 134.25	INDIANAPOLIS APP CON 128.175 317.8	INDY TOWER 120.9 257.8	GND CON 121.9	CLNC DEL 128.75 257.8	CPDLC
------------------	---------------------------------------	---------------------------	------------------	--------------------------	-------

The main chart displays the RNP Z RWY 32 procedure. Key features include:

- Initial Approach:** Starts at 1159, descends to 1150, then to 897±. A missed approach fix is shown with a 4 NM radius and 139°/319° angles.
- Intermediate Approach:** Passes RW32 (811), then DLNGR, and CUREG (200K). Altitudes are 1546, 1400 (13.3), 3600 (20.5), and 3000 (12.9).
- Final Approach:** Passes BTTLR (2400), EVAVE (200K), and HIKEK. Altitudes are 1252, 2400 (14.6), 3600 (2.9), and 3000 (07.5).
- Obstacles:** Various obstacles are marked with their MSL and AGL altitudes, including (IF) PNFLD, (IF) HNKLE, (IF) OZMOE, and (IF) BDAWG.
- MSA:** A Minimum Safe Altitude circle is shown with a radius of 25 NM and a value of 3100.
- Waypoints:** KEADY, BTTLR, EVAVE, HIKEK, and CUREG are marked as key waypoints.

ELEV 796

D

TDZE 793

Planview diagram showing the glidepath and various altitudes. Key features include:

- Altitudes:** 3000, 2400, 2000, 1700, 1500, 1300, 1100.
- Angles:** 320°, 139°, 319°.
- Distances:** 4.9 NM, 4.2 NM, 2.9 NM.
- Waypoints:** KEADY, BTTLR, EVAVE, HIKEK, CUREG.

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 73).

BTTLR

2400

GP 3.00°

TCH 53

CATEGORY	A	B	C	D
RNP 0.19 DA	1134/30	341 (400-%)		
RNP 0.30 DA	1196/45	403 (400-%)		

AUTHORIZATION REQUIRED

INDIANAPOLIS, INDIANA

Amdt 2 10NOV16

39°43'N-86°18'W

INDIANAPOLIS INTL (IND)

RNAV (RNP) Z RWY 32