

WAAS
CH **61329**
W16A

APP CRS
166°

Rwy Idg
TDZE
Apt Elev

9501
2872
2872

RNAV (GPS) RWY 16R

MIDLAND INTL AIR AND SPACE PORT (M.A.F.)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11°C (13°F) or above 25°C (77°F). Rwy 16R helicopter visibility reduction below ¾ SM NA. DME/DME RNP-0.3 NA. Circling Rwy 16L NA at night.

MISSED APPROACH: Climb to 4700 direct ICORO and hold.

ATIS 126.8 235.975	MIDLAND APP CON* 124.6 290.4	MIDLAND TOWER* 118.7 (CTAF) 0273.45	GND CON 121.9 348.6	CLNC DEL 118.05 317.65	UNICOM 122.95
------------------------------	--	---	-------------------------------	----------------------------------	-------------------------

5 NM Holding Pattern		PERAE		SIXVE		RW16R		ICORO					
5100		166°		4600		*1.4 NM to RW16R		*LNAV only					
GP 3.00°		TCH 50		7.3 NM		3.9 NM		1.4 NM					
CATEGORY	A	B	C	D									
LPV DA	3072-¾		200 (200-¾)										
LNAV/VNAV DA	3398-1¾		526 (600-1¾)										
LNAV MDA	3360-1	488 (500-1)	3360-1¾	488 (500-1¾)									
CIRCLING	3440-1	568 (600-1)	3440-1½	568 (600-1½)	3520-2	648 (700-2)							

MIDLAND, TEXAS

Amdt 1B 22JUN17

MIDLAND INTL AIR AND SPACE PORT (M.A.F.)

31°57'N-102°12'W

RNAV (GPS) RWY 16R