RNAV (GPS) RWY 22

MIDLAND INTL AIR AND SPACE PORT (MAF)

WAAS	APP CRS	Rwy Idg	4605
CH 50429	225°	TDZE	2855
W22A		Apt Elev	2872

RNP APCH.

T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11°C or above 25°C. Circling Rwy 16L NA at night.

MISSED APPROACH: Climb to 5000 direct TOKRE and hold.

ATIS	MIDLAND APP CON ★	MIDLAND TOWER ★	GND CON	CLNC DEL	UNICOM
126.8 235.975	124.6 290.4	118.7 (CTAF) L 273.45	121.9 348.6	118.05 317.65	122.95





CATEGORY	A	B	C	D
LPV DA	3055-¾ 200 (200-¾)			
LNAV/VNAV DA	3317-1⅜ 462 (500-1⅜)			
LNAV MDA	3320-1 465 (500-1)		3320-1⅜ 465 (500-1⅜)	
C CIRCLING	3440-1 568 (600-1)		3440-1½ 568 (600-1½)	3520-2 648 (700-2)

ELEV 2872 D TDZE 2855



REIL Rwy 34L
MIRL Rwys 4-22 and 16L-34R L
HIRL Rwys 10-28 and 16R-34L

SC-3, 18 APR 2024 to 16 MAY 2024
SC-3, 18 APR 2024 to 16 MAY 2024