

APP CRS	Rwy Idg	8995
227°	TDZE	26
	Apt Elev	27

RNAV (RNP) Y RWY 23

NORFOLK INTL (ORF)

▼

For uncompensated Baro-VNAV systems, procedure NA below -9°C (16°F) or above 54°C (130°F). GPS required. For inop ALS, increase RNP 0.10 DA visibility all Cats to 1½ SM, increase RNP 0.30 DA visibility all Cats to 1¾ SM.

MALSR

MISSED APPROACH: Climb to 2000 on track 227° to CALEY and hold.

ATIS 127.15	NORFOLK APP CON 118.9 353.7	NORFOLK TOWER 120.8 257.8	GND CON 121.9	CLNC DEL 118.5
----------------	--------------------------------	------------------------------	------------------	-------------------

RADAR REQUIRED

ELEV 27

D

TDZE 26

2000

↑

tr 227°

CALEY

△

See planview for multiple IF locations.

BAAGN

1200

1200

GP 3.00°

TCH 55

3.6 NM

CATEGORY	A	B	C	D
RNP 0.10 DA		432-¾	406 (500-¾)	
RNP 0.30 DA		491-1	465 (500-1)	

AUTHORIZATION REQUIRED

REIL Rwy 14 and 32

HIRL Rwy 5-23

MIRL Rwy 14-32

NORFOLK, VIRGINIA

Amtd 1 01FEB18

36°54'N-76°12'W

NORFOLK INTL (ORF)

RNAV (RNP) Y RWY 23