RNAV (GPS) X RWY 17R

RENO/TAHOE INTL (RNO)

WAAS	APP CRS	Rwy Idg	10001
CH 78309	167°	TDZE	4415
W17B		Apt Elev	4415

RNP APCH - GPS.

For inop ALS, increase LPV all Cats visibility to 2½ SM. Inop table does not apply to LNAV all Cats.

MALSR

MISSED APPROACH: Climb to 13000 direct ZEXUT and on track 161° to MARRI and hold.

D-ATIS	NORCAL APP CON	RENO TOWER	GND CON	CLNC DEL	CPDLC
135.8 363.0	119.2 279.55 126.3 353.9	118.7 257.8	121.9 348.6	124.9 370.85	



ELEV 4415 TDZ 4415

D



MIRL Rwy 8-26
REIL Rwys 8, 17L, 26, and 35R
HIRL Rwys 17R-35L and 17L-35R

13000	ZEXUT	tr 161°	MARRI

VGSI and RNAV glidepath not coincident (VGSI Angle 3.06/TCH 77).



CATEGORY	A	B	C	D
LPV DA	5239-1⅞ 824 (900-1⅞)			
LNAV MDA	6200/40 1785 (1800-¾)	6200/55 1785 (1800-1)	6200-3 1785 (1800-3)	

SW-4, 18 APR 2024 to 16 MAY 2024