

LOC/DME I-OGZ
111.95
Chan **56**(Y)

APP CRS
123°

Rwy Idg
TDZE **618**
Apt Elev **618**

ILS or LOC RWY 11

ST LOUIS LAMBERT INTL (STL)

RADAR required for procedure entry. DME or RADAR required.

⚠

Simultaneous approach authorized with Rwy 12R/L. Disregard OM signal associated with ILS to Rwy 12R. For inop ALS, increase S-ILS Cat E visibility to RVR 4000, and S-LOC Cat C/D/E visibility to RVR 5500.

ALSF-2

MISSED APPROACH: Climb to 1060 then climbing right turn to 3000 on heading 130° and FTZ R-095 to MOODS INT/FTZ 44.7 DME and hold.

D-ATIS 125.025 379.925	ST. LOUIS APP CON 132.125 360.6	ST. LOUIS TOWER 132.475 239.275	GND CON 121.9 348.6 (Inbound) 121.65 377.175 (Outbound) 118.925 227.125 (Rwy 11/29)	CLNC DEL 119.5 363.1	CPDLC
--	---	---	---	--------------------------------	-------

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 67).					
SISDE INT I-OGZ 17.8 ZOVUN I-OGZ 14.9 HIXOB I-OGZ 10.4 JEXAR I-OGZ 7.4 *I-OGZ 2.7 I-OGZ 1.8					
5000 123° 5000 3500 2500 1060 3000 FTZ R-095 MOODS					
GS 3.00° TCH 55 2.9 NM 4.4 NM 3 NM 4.6 NM 0.9 NM 0.1 NM					
CATEGORY	A	B	C	D	E
S-ILS 11	818/18 200 (200-½)				
S-LOC 11	980/24 362 (400-½)		980/35 362 (400-¾)		

ELEV 618 TDZE 618

Rwy 6-24 7603 X 150
Rwy 11-29 9000 X 150
Rwy 12L-30R 9013 X 150
Rwy 12R-30L 11020 X 150

HIRL all Rwy's
TDZ/CL Rwy's 11, 12L, 12R, 29, and 30R
FAF to MAP 5.6 NM

Knots	60	90	120	150	180
Min:Sec	5:36	3:44	2:48	2:14	1:52

ST. LOUIS, MISSOURI
Amdt 1 03JAN19

38°45'N-90°22'W

ST LOUIS LAMBERT INTL (STL)
ILS or LOC RWY 11