ILS or LOC RWY 29

ST LOUIS LAMBERT INTL (STL)

LOC/DME I-RQN	APP CRS	Rwy Idg	9000
111.95	303°	TDZE	580
Chan 56(Y)		Apt Elev	618

RADAR required for procedure entry. DME or RADAR required.

T Simultaneous approach authorized with Rwy 30R/L. Autopilot coupled approach NA. Rwy 29 helicopter visibility reduction below RVR 4000 NA. For inop ALS, increase S-ILS Cat E visibility to RVR 4000, increase S-LOC Cats A/B visibility to RVR 5500, and Cat C/D/E to RVR 6000.

ALSF-2

MISSED APPROACH: Climb to 1040 then climbing left turn to 3000 on heading 286° and on TOY VORTAC R-272 to HULSO/TOY 36.7 DME and hold.

D-ATIS	ST. LOUIS APP CON	ST. LOUIS TOWER	GND CON	CLNC DEL	CPDLC
125.025 379.925	132.125 360.6	132.475 239.275	121.9 348.6 (Inbound) 121.65 377.175 (Outbound) 118.925 227.125 (Rwy 11/29)	119.5 363.1	



ELEV 618	D	TDZE 580

Rwy 6-24 7603 X 150
Rwy 11-29 9000 X 150
Rwy 12L-30R 9013 X 150
Rwy 12R-30L 11020 X 150



HIRL all Rwys
TDZ/CL Rwys 11, 12L, 12R, 29, and 30R

FAF to MAP 5.2 NM					
Knots	60	90	120	150	180
Min:Sec	5:12	3:28	2:36	2:05	1:44

1040	3000 hdg 286°	TOY R-272	HULSO TOY 36.7

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/ TCH 73).

Disregard OM indications.
* LOC only



CATEGORY	A	B	C	D	E
S-ILS 29	780/18 200 (200-½)				
S-LOC 29	980/40 400 (400-¾)				

NC-3, 18 APR 2024 to 16 MAY 2024
NC-3, 18 APR 2024 to 16 MAY 2024