APP CRS	Rwy Idg	8956
123°	TDZE	541
	Apt Elev	618

RNAV (RNP) Z RWY 12L

ST LOUIS LAMBERT INTL (STL)

For uncompensated Baro-VNAV systems, procedure NA below -16°C (4°F) or above 54°C (130°F). GPS required. For inop ALS, increase RNP 0.30 all Cats visibility to 1¾ SM. Simultaneous approach authorized with Rwy 11, except for arrivals at RRIPP and HRBEE. Use of FD or AP required during simultaneous operations.

ALSF-2

MISSED APPROACH: Climb to 3000 on track 123° to ODITY and on track 071° to TOY VORTAC and hold.

D-ATIS	ST. LOUIS APP CON	ST. LOUIS TOWER	GND CON	CLNC DEL	CPDLC
125.025 379.925	132.125 360.6	120.05 284.6	121.9 348.6 (Inbound) 121.65 377.175 (Outbound) 118.925 227.125 (Rwy 11/29)	119.5 363.1	

RADAR REQUIRED

MSA RW12L 25 NM
3000

(IAF) VEEGE 9000 250K 8000
5500
148° (10.3)
YADDI
1150
4000
148°
(5.7)
(IF) CORDL 250K
(IAF) RUYON 6000 250K
4200
123°
(5.6)
3400
148°
(6.2)
(IF) EUBIE 250K
3400
123°
(4.4)
2400 123° (2.8)
2400 (8.7)
BUFEE 210K
5000
301° (2.9)
(IF) HRBEE 5000 250K (RF REQD)
6000
084° (5.5)
4000
084°
(4.2)
3400
084°
(6.9)
FARIS 250K
(IF) AARBY 250K
KARRP 250K
(IAF) STAAN 7000 250K
(FAF) OHROB 165K
1700
123°
(2.6)
KIRKA 210K
793
(3.5)
123°
2400
(8.2)
RW12L
MISSED APCH FIX
TROY
TOY
083°
263°
4 NM
SSAMM 210K
897
875
5000
303° (2.9)
(IF) RRIPP 5000 250K (RF REQD)
1017
123°
(9.9)
(13.4)
071°
ODITY

ELEV 618 D TDZE 541

Rwy 6-24 7603 X 150
Rwy 11-29 9000 X 150
Rwy 12L-30R 9013 X 150
Rwy 12R-30L 11020 X 150

123°



HIRL all Rwys
TDZ/CL Rwys 11, 12L, 12R, 29, and 30R



CATEGORY	A	B	C	D
RNP 0.30 DA	1043/60 502 (500-1¼)			

AUTHORIZATION REQUIRED

NC-3, 18 APR 2024 to 16 MAY 2024
NC-3, 18 APR 2024 to 16 MAY 2024