WAAS	APP CRS		
CH **69499**	**123°**	Rwy Idg	**8956**
W12A		TDZE	**541**
		Apt Elev	**618**

RNAV (GPS) Y RWY 12L

ST LOUIS LAMBERT INTL (STL)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inop ALS, increase LPV all Cats visibility to 1½ SM, LNAV/VNAV Cat E visibility to 1¾ SM, and LNAV Cat E visibility to 1¾ SM. Simultaneous approach authorized with Rwy 11. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations.

ALSF-2

MISSED APPROACH: Climb to 3000 direct ODITY and on track 071° to TOY VORTAC and hold.

D-ATIS	ST. LOUIS APP CON	ST. LOUIS TOWER	GND CON	CLNC DEL	CPDLC
125.025 **379.925**	**132.125** **360.6**	**120.05** **284.6**	**121.9** **348.6** (Inbound) **121.65** **377.175** (Outbound) **118.925** **227.125** (Rwy 11/29)	**119.5** **363.1**	

RADAR REQUIRED

(IAF) RUYON

4000 123° (5.6)

(IF) EUBIE

2500 123° (7.4)

(FAF) GREEP

1128

793

897

875

1017

RW12L

MISSED APCH FIX TROY TOY 083° 263° 4 NM

071° (13.4) ODITY

MSA RW12L 25 NM 3000

ELEV 618 D TDZE 541

Rwy 6-24 7603 X 150
Rwy 11-29 9000 X 150
Rwy 12L-30R 9013 X 150
Rwy 12R-30L 11020 X 150

123°

TWR 774

HIRL all Rwys
TDZ/CL Rwys 11, 12L, 12R, 29, and 30R

	3000	ODITY	tr 071°	TOY

RUYON 5000 123° EUBIE 4000 GREEP 2500 *1.4 NM to RW12L RW12L 2500 *LNAV only

GP 3.00° TCH 54

5.6 NM 7.4 NM 4.5 NM 1.4 NM

CATEGORY	A	B	C	D	E
LPV DA	951/50 410 (400-1)				
LNAV/VNAV DA	1040/60 499 (500-1¼)				
LNAV MDA	1040/24 499 (500-½)		1040/40 499 (500-¾)	1040/50 499 (500-1)	1040/60 499 (500-1¼)

NC-3, 18 APR 2024 to 16 MAY 2024
NC-3, 18 APR 2024 to 16 MAY 2024