RNAV (GPS) Y RWY 12R

ST LOUIS LAMBERT INTL (STL)

WAAS CH 78121 W12B	APP CRS 123°	Rwy ldg 10553 TDZE 540 Apt Elev 618

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130° F). DME/DME RNP-0.3 NA. For inop ALS, increase LPV Cat E visibility to RVR 4000, LNAV Cats A/B visibility to RVR 5000, and LNAV Cat E visibility to 1½ SM. Inop table does not apply to LNAV/VNAV. Simultaneous approach authorized with Rwy 11. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations.

MALSR (A5)

MISSED APPROACH: Climb to 5000 direct FONTI and hold, continue climb-in-hold to 5000.

D-ATIS	ST. LOUIS APP CON	ST. LOUIS TOWER	GND CON	CLNC DEL	CPDLC
125.025 379.925	132.125 360.6	118.5 257.7	121.9 348.6 (Inbound) 121.65 377.175 (Outbound) 118.925 227.125 (Rwy 11/29)	119.5 363.1	



ELEV 618 D TDZE 540



HIRL all Rwys
TDZ/CL Rwys 11, 12L, 12R, 29, and 30R



CATEGORY	A	B	C	D	E
LPV DA	740/18 200 (200-½)				
LNAV/VNAV DA	1103-2 563 (500-2)				
LNAV MDA	1000/40 460 (400-¾)			1000/50 460 (400-1)	

NC-3, 18 APR 2024 to 16 MAY 2024
NC-3, 18 APR 2024 to 16 MAY 2024