

HI-ILS or LOC RWY 10

LOC I-SAV
111.35
Chan**50 (Y)**

APCH CRS
097°

Rwy Idg
TDZE
Arpt Elev

9351
30
50

AL-380 [USAF]

SAVANNAH/HILTON HEAD INTL (KSAV)

DME required

Procedure NA when Control Tower closed.
* When ALS inop, increase vis to RVR 40
** When ALS inop, increase vis to 1½ miles.

MALSRL
5

MISSED APPROACH: Climb to 800, then climbing left turn to 4000 via heading 330° and SAV VORTAC R-001 to TILLS/SAV 20 DME and hold.

ATIS ★
123.75

APP CON
125.3 353.775

TOWER ★
125.975 (CTAF) 257.8

GND CON
121.9 348.6

CLNC DEL
119.55 291.775

• 361

SAVANNAH
115.95 SAV
Chan 106 (Y)

LOCALIZER 111.35
I-SAV
Chan 50 (Y)

EMERG SAFE ALT 100 NM 3100

Use I-SAV DME when on the localizer course.
VGSI and ILS glidepath not coincident.
VGSI angle 3.00/TCH 69.

FILOX R-316 5000

GEKME 25

WADEB 25

MIRPE I-SAV 13.7

SOVIE I-SAV 7.7

FAPLI 10

VORTAC

RICKY 7

TILLS SAV R-001 20

800

4000

SAV R-001

TILLS SAV R-001 20

ELEV 50

D

TDZE 30

61

TWR 216

9351 x 150

0.3° UP

7002 x 150

097°

117

134

28

1

CATEGORY	C	D	E
S-ILS 10 *	230/18	200	(200-½)
S-LOC 10 **	500/50	470	(500-1)
CIRCLING	740-2 690 (700-2)	740-2¼ 690 (700-2¼)	900-3 850 (900-3)

REIL Rwy 19, 28
HIRL all Rwy
TDZL/CL Rwy 10

SAVANNAH, GEORGIA

32° 08' N-81° 12' W

SAVANNAH/HILTON HEAD INTL (KSAV)

Amdt 8 08NOV18

HI-ILS or LOC RWY 10

SE-4, 18 APR 2024 to 16 MAY 2024

SE-4, 18 APR 2024 to 16 MAY 2024