RNAV (GPS) RWY 1

SAVANNAH/HILTON HEAD INTL (SAV)

WAAS CH 45515 W01A	APP CRS 006°	Rwy Idg 7002 / TDZE 39 / Apt Elev 50

RNP APCH.

T A — For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 49°C (120°F).

MISSED APPROACH: Climb to 2500 direct SUTME and hold.

ATIS	SAVANNAH APP CON★	SAVANNAH TOWER★	GND CON	CLNC DEL	UNICOM
123.75	120.4 353.775	125.975 (CTAF) L 257.8	121.9 348.6	119.55 291.775	122.95



ELEV 50 | D | TDZE 39



TDZ/CL Rwy 10
REIL Rwys 19 and 28 L
HIRL Rwys 1-19 and 10-28 L

2500 | SUTME

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 74).



CATEGORY	A	B	C	D
LPV DA	239/40 200 (200-¾)			
LNAV/VNAV DA	384/60 345 (400-1¼)			
LNAV MDA	520/55 481 (500-1)		520-1⅜ 481 (500-1⅜)	
C CIRCLING	520-1 470 (500-1)		740-2 690 (700-2)	740-2¼ 690 (700-2¼)

SE-4, 18 APR 2024 to 16 MAY 2024
SE-4, 18 APR 2024 to 16 MAY 2024