APP CRS	Rwy Idg	10996
123°	TDZE	2599
	Apt Elev	2643

RNAV (RNP) Y RWY 11L

TUCSON INTL (TUS)

RNP AR APCH.

T A NA For uncompensated Baro-VNAV systems, procedure NA below -3°C or above 52°C. For inoperative MALSR, increase RNP 0.30 visibility to RVR 6000 all Cats. GPS required.

MALSR

MISSED APPROACH: Climb to 6000 via 123° track to CURGA, 213° track to REBDE, 303° track to TOYOP and hold.

ATIS	TUCSON APP CON	TUCSON TOWER	GND CON	CLNC DEL
123.8 279.65	119.4 318.1	118.3 257.8	120.025 348.6	126.65 326.2



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 73).

6000	CURGA	213°	REBDE	303°	TOYOP
123° tr		tr		tr	



CATEGORY	A	B	C	D
RNP 0.30 DA	2947/40 348 (400-¾)			

AUTHORIZATION REQUIRED



HIRL Rwy 12-30
MIRL Rwy 4-22
REIL Rwys 22 and 30

SW-4, 18 APR 2024 to 16 MAY 2024
SW-4, 18 APR 2024 to 16 MAY 2024