LOC/DME I-ASO	APP CRS	Rwy Idg	6869
109.9	149°	TDZE	13
Chan 36		Apt Elev	14

LDA Y RWY 19

RONALD REAGAN WASHINGTON NTL (DCA)

Inoperative table does not apply.
Circling NA northeast of Rwy 15-33.
ADF or DME required.

MALSF

MISSED APPROACH: Climb to 1800 direct DCA VOR/DME and on DCA VOR/DME R-185 to OXONN NDB/DCA 5.6 DME and hold.

D-ATIS	POTOMAC APP CON			WASHINGTON TOWER	GND CON	CLNC DEL	CPDLC
132.65	119.85	239.25	(WEST/SOUTH)	119.1 257.6	121.7 257.6	128.25	
	124.2	360.8	(EAST)				

Prohibited Area (P-56) 1.5 NM north of DCA - Avoid Surface to 18000 MSL.

329°

(IF)
CROOZ
I-ASO 17
RADAR

3000
149°
(7)

MAUDY INT
I-ASO 10

2000
149°
(3.7)

MINIE INT
I-ASO 6.3

JEVGA INT
I-ASO 3.5

R-256 115.1 BAL Chan 98

R-249 115.1 BAL Chan 98

R-242 115.1 BAL Chan 98

940 1052 1102 987 548 897 866 1050 590 434 594 674 450

416± 370± 595

P-56B P-56A

LOCALIZER 109.9
I-ASO
Chan 36
LOC offset 37.50°.

RADAR REQUIRED

MSA DCA 25 NM
2600

Fly visual
149° 3.4 NM

440

R-185

WASHINGTON
111.0 DCA
Chan 47

OXONN
332 DCA

OXONN
DCA 5.6

185°

005°

P-73

ELEV 14 D TDZE 13

149°

15 6 33 24 22 4 1

TWR
229

7169 X 150

3000 X 150

TDZ/CL Rwy 1
MIRL Rwy 4-22
REIL Rwys 4, 22, 15 and 33
HIRL Rwys 1-19 and 15-33

1800 DCA DCA R-185 DCA

CROOZ
I-ASO 17
RADAR

MAUDY INT
I-ASO 10

MINIE INT
I-ASO 6.3

JEVGA INT
I-ASO 3.5

Fly visual
149° 3.4 NM

3000 149° 3000 149° 2000

7 NM 3.7 NM 2.8 NM 3.4 NM

FAF to MAP 2.8 NM

Knots	60	90	120	150	180
Min:Sec	2:48	1:52	1:24	1:07	0:56

CATEGORY	A	B	C	D
S-LDA 19	1100-3 1087 (1100-3)			
C CIRCLING	1100-3 1086 (1100-3)			

NE-3, 18 APR 2024 to 16 MAY 2024