RNAV (RNP) RWY 1

RONALD REAGAN WASHINGTON NTL (DCA)

APP CRS	Rwy ldg	6869
007°	TDZE	14
	Apt Elev	14

For uncompensated Baro-VNAV systems, procedure NA below -10°C (14°F) or above 48°C (120°F). RF required. GPS required. Missed approach requires RNP less than 1.0. For inop ALS, increase RNP 0.30 all Cats visibility to 1¾ mile.

ALSF-2

MISSED APPROACH: (Do not exceed 185K until FIVUD) Climb to 2200 left turn to FIVUD and on track 327° to HESLO and on track 327° to GTN NDB and hold.

D-ATIS	POTOMAC APP CON			WASHINGTON TOWER	GND CON	CLNC DEL	CPDLC
132.65	119.85	239.25	(WEST/SOUTH)	119.1 257.6	121.7 257.6	128.25	
	124.2	360.8	(EAST)				

MISSED APCH FIX

147°
4 NM
327°

GEORGETOWN GTN

897 1050 866 416± 595 327° (1.3) (2.2) 370± 590 674 434 594 194 440 450

P-56B 327° (3.3) HESLO P-56A FIVUD RW01

(FAF) BADDN

Prohibited area (P-56) 1.5 NM north of DCA- avoid surface to 18000 MSL.

P-73

007° (5.8) 1600

(IF) MRION

2500 038° (3.6)

JWASH

3500 038° (5.4)

(IAF) IRONS

MSA RW01 25 NM 2100

ELEV 14 D TDZE 14

REIL Rwys 4, 22, 15 and 33
HIRL Rwys 1-19 and 15-33
MIRL Rwy 4-22
TDZ/CL Rwy 1





CATEGORY	A	B	C	D
RNP 0.30 DA	552/60		538 (600-1¼)	

AUTHORIZATION REQUIRED

NE-3, 18 APR 2024 to 16 MAY 2024
NE-3, 18 APR 2024 to 16 MAY 2024