

WAAS CH 77530 W18B	APP CRS 175°	Rwy Idg 12250 TDZE 542 Apt Elev 542
--	------------------------	--

RNAV (GPS) Y RWY 18R

AUSTIN-BERGSTROM INTL (AUS)

RNP APCH-GPS.

Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. Inop table does not apply to LPV. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4500; increase LNAV Cat E visibility to RVR 5500.

MALS

MISSED APPROACH: Climb to 1000 then climbing right turn to 3500 direct GARDS and hold.

D-ATIS 124.4	AUSTIN APP CON 127.225 317.65 (EAST) 120.875 270.25 (SOUTH) 119.0 370.85 (WEST)	AUSTIN TOWER 121.0 281.5	GND CON 121.9 348.6	CLNC DEL 125.5 263.0	CPDLC
------------------------	---	------------------------------------	-------------------------------	--------------------------------	-------

Enroute stage: (IAF) HOUKM 5000 210K, (IAF) CHADE 2800 175 (5.5), (IAF) JEDYE 4000 210K. Intermediate stage: (IF) UTEEE 1600 175 (3.8), (FAF) ELLBJ 661 580. Final approach: RW18R. Altitudes: 1402, 1638, 1448, 1158, 846, 819, 842. Distances: 3.8 NM, 2.2 NM, 0.9 NM. Navigational aids: GARDS (042, 222, 6 NM), MSA RW18R 25 NM (3100).

UTEEE	ELLBJ	1000	3500	GARDS	
2800	1600				
GP 3.00°					
TCH 59					
3.8 NM	2.2 NM	0.9 NM			
CATEGORY	A	B	C	D	E
LPV DA		742/40	200 (200-¾)		
LNAV/VNAV DA		834/40	292 (300-¾)		
LNAV MDA		900/40	358 (400-¾)		
CIRCLING	1040-1 498 (500-1)	1120-1 578 (600-1)	1200-1¾ 658 (700-1¾)	1200-2 658 (700-2)	1520-3 978 (1000-3)

Final approach: RW18R. Altitudes: 181, 12250 X 150, 680, 36L, 36R. Distances: 0.9 NM, 0.3% UP, 0.3% DOWN. Navigational aids: TW R 727, MSA RW18R 25 NM (3100).

AUSTIN, TEXAS
Amdt 3A 14JUL22

30°12'N-97°40'W

AUSTIN-BERGSTROM INTL (AUS)

RNAV (GPS) Y RWY 18R

SC-3, 18 APR 2024 to 16 MAY 2024

SC-3, 18 APR 2024 to 16 MAY 2024