RNAV (GPS) RWY 36L

ORLANDO INTL (MCO)

WAAS	APP CRS	Rwy Idg 11621
CH 82313	005°	TDZE 93
W36B		Apt Elev 96

RNP APCH.

T Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 1°C or above 54°C.

MISSED APPROACH: Climb to 500 then climbing left turn to 3000 direct DNMOR and hold, continue climb-in-hold to 3000.

D-ATIS	ORLANDO APP CON	ORLANDO TOWER	GND CON	CLNC DEL	
ARR 121.25	124.8 307.0	118.45 253.5 (Rwys 17L-35R,17R-35L)	126.4 (East)	134.7	CPDLC
DEP 120.525		124.3 253.5 (Rwys 18L-36R,18R-36L)	121.8 (West)	341.7	





CATEGORY	A	B	C	D
LPV DA		293/40	200 (200-¾)	
LNAV/VNAV DA		406/45	313 (400-⅞)	
LNAV MDA	480/55	387 (400-1)	480/60	387 (400-1¼)
C CIRCLING	740-1	644 (700-1)	740-1¾ 644 (700-1¾)	740-2 644 (700-2)



SE-3, 18 APR 2024 to 16 MAY 2024
SE-3, 18 APR 2024 to 16 MAY 2024