RNAV (GPS) Y RWY 11

LOUIS ARMSTRONG NEW ORLEANS INTL (MSY)

WAAS	APP CRS	Rwy Idg	9800
CH 61319	106°	TDZE	4
W11A		Apt Elev	4

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1°C (31°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inop ALSF-2, increase LNAV/VNAV all Cats visibility to RVR 4000.

ALSF-2

MISSED APPROACH: Climb to 2000 direct ZUBEL and on track 195° to SAFES and hold.

D-ATIS	NEW ORLEANS APP CON	NEW ORLEANS TOWER	GND CON	CLNC DEL	CPDLC
127.55	WEST 125.5 350.35 EAST 133.15 290.3	119.5 254.3	121.9 273.525	120.925	



ELEV 4 | D | TDZE 4



RLLS Rwy 2
TDZ/CL Rwy 11
HIRL All Runways



CATEGORY	A	B	C	D
LPV DA	204/18 200 (200-½)			
LNAV/VNAV DA	254/24 250 (300-½)			
LNAV MDA	340/24 336 (400-½)		340/26 336 (400-½)	
C CIRCLING	520-1 516 (600-1)		580-1½ 576 (600-1½)	600-2 596 (600-2)

SC-4, 18 APR 2024 to 16 MAY 2024
SC-4, 18 APR 2024 to 16 MAY 2024