ILS or LOC RWY 4L

JOHN F KENNEDY INTL (JFK)

LOC/DME I-HIQ	APP CRS	Rwy Idg 11010
110.9	044°	TDZE 13
Chan 46		Apt Elev 13

RADAR required for procedure entry. DME or RADAR required for LOC only.

Simultaneous approach authorized.
Autopilot coupled approach NA below 200 feet MSL.

MISSED APPROACH: Climb to 2000 then climbing right turn to 3000 on JFK VOR/DME R-062 to DUFFY INT/JFK 14.8 DME and hold.

D-ATIS (ARR/DEP)	(ARR-NE)	(ARR-SW)	NEW YORK APP CON		KENNEDY TOWER		GND CON	CLNC DEL	CPDLC
128.725	117.7	115.4	128.125	269.0	Rwys 4R/22L and 13L/31R	119.1 281.55	121.9	135.05	
					Rwys 4L/22R and 13R/31L	123.9 281.55	348.6	348.6	







CATEGORY	A	B	C	D
S-ILS 4L	231/40	218 (300-¾)		
S-LOC 4L	460/55	447 (500-1)	460-1⅜	447 (500-1⅜)
C CIRCLING	640-1	627 (700-1)	700-2	700-2¼
			687 (700-2)	687 (700-2¼)

FAF to MAP 4.5 NM

Knots	60	90	120	150	180
Min:Sec	4:30	3:00	2:15	1:48	1:30

NE-2, 18 APR 2024 to 16 MAY 2024
NE-2, 18 APR 2024 to 16 MAY 2024