RNAV (GPS) Z RWY 13R

JOHN F KENNEDY INTL (JFK)

APP CRS	Rwy Idg	12467
134°	TDZE	13
	Apt Elev	13

RNP APCH - GPS.

RADAR required.

MISSED APPROACH: (Do not exceed 185K until RW13R). Climb to 1300 on FMS lateral path to RW13R, then climb to 2000 direct ZACHS and hold. If unable to follow the FMS lateral path, turn right heading 134° and climb to 2000 direct ZACHS hold.

D-ATIS (ARR/DEP)	(ARR-NE)	(ARR-SW)	NEW YORK APP CON	KENNEDY TOWER		GND CON	CLNC DEL	CPDLC
128.725	117.7	115.4	128.125 269.0	Rwys 4R/22L and 13L/31R	119.1 281.55	121.9	135.05	
				Rwys 4L/22R and 13R/31L	123.9 281.55	348.6	348.6	

MISSED APCH FIX

Cross PEEBO, fly visual to airport along depicted track 089° to MAYMA then track 134° to RWY 13R.

O Lead-in light groups

Turns required in the visual segment.







CATEGORY	A	B	C	D
LNAV MDA	940-3	927 (1000-3)		

RLLS Rwys 13L and 13R
HIRL all Rwys
TDZ/CL Rwys 4L, 4R, 13L, 22L and 31R

NE-2, 18 APR 2024 to 16 MAY 2024
NE-2, 18 APR 2024 to 16 MAY 2024