

LOC I-JDP <u>108.7</u>	APP CRS 276°	Rwy Idg 12000 TDZE 875 Apt Elev 896
----------------------------------	------------------------	--

ILS or LOC RWY 27

CINCINNATI/NORTHERN KENTUCKY INTL (CVG)

RADAR required for procedure entry.

T For inop ALS, increase S-LOC 27 Cat C/D visibility to 1 $\frac{3}{8}$ SM.
 ** RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 2000 then climbing left turn to 3000 on heading 230° and CVG R-244 to AVIEW INT/CVG 20 DME and hold.

D-ATIS		CINCINNATI APP CON		CINCINNATI TOWER		GND CON	CLNC DEL	CPDLC
ARR	DEP	119.7	363.15 (090°-269°)	118.975	360.85 (RWY 18L/36R)			
134.375	135.3	123.875	363.15 (270°-089°)	118.3	(RWYS 18C/36C, 09/27)	121.7	127.175	
MISSED APCH FIX				133.325 (RWY 18R/36L)		CVG 25		

MISSED APCH FIX

MSA CVG 25 NM

2900

LOCALIZER 108.7

LIDB ::


CINCINNATI

ALTERNATE
MISSED APCH FIX

FALMOUTH
FLM   
117.0
Chan 117

R-324-144°
324° 

ELEV	896	D	TDZE	875
------	-----	----------	------	-----



HIRL all Rwys
TDZ/CL all Rwys except 27

FAF to MAP 4.6 NM

Knots	60	90	120	150	180
Min:Sec	4:36	3:04	2:18	1:50	1:32

CATEGORY	A	B	C	D
S-ILS 27 **	1075/24 200 (200-½)			
S-LOC 27	1340/24	465 (500-½)	1340/50	465 (500-1)
 CIRCLING	1460-1	564 (600-1)	1560-1¾ 664 (700-1¾)	1560-2 664 (700-2)