RNAV (GPS) RWY 1R

HARRY REID INTL (LAS)

WAAS CH 42800 W01A	APP CRS 014°	Rwy Idg 8785 TDZE 2170 Apt Elev 2181

RNP APCH-GPS. RADAR required.

Rwy 1R helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1°C or above 54°C.

MISSED APPROACH: Climb to 2700 then climbing right turn to 7000 direct HAIDN and hold, continue climb-in-hold to 7000.

D-ATIS	LAS VEGAS APP CON	LAS VEGAS TOWER	GND CON	CLNC DEL	CPDLC
132.4	125.025 379.15 (West) 119.775 282.2 (East)	118.75 257.8 (Rwy 1L/19R, 1R/19L) 119.9 257.8 (Rwy 8L/26R, 8R/26L)	121.1 270.8 E of 1R/19L 121.9 254.3 W of 1R/19L	118.0	





CATEGORY	A	B	C	D
LPV DA	2458-⅞ 288 (300-⅞)			
LNAV/VNAV DA	2641-1⅜ 471 (500-1⅜)			
LNAV MDA	2820-1 650 (700-1)		2820-1⅞ 650 (700-1⅞)	
C CIRCLING	3020-1¼ 839 (900-1¼)	3060-1¼ 879 (900-1¼)	3100-2¾ 919 (1000-2¾)	3540-3 1359 (1400-3)



SW-4, 18 APR 2024 to 16 MAY 2024