LOC RWY 35

NORWOOD MEML (OWD)

LOC/DME I-OWD	APP CRS	Rwy Idg	4007
108.3	350°	TDZE	49
Chan 20		Apt Elev	49

ADF or DME required.

MALSF

MISSED APPROACH: Climbing left turn to 3000 and BOS VOR/DME R-240 to MILIS INT/20.9 DME and hold, continue climb-in-hold to 3000.

Helicopter visibility reduction below ¾ SM NA. DIKEY fix minimums: For inop ALS, increase S-35 Cat C/D visibility to 1⅜ SM. Circling NA at night.

ATIS	BOSTON APP CON	NORWOOD TOWER ★	GND CON	CLNC DEL
119.95	124.1 263.1	126.0 (CTAF) L	121.8	121.8





CATEGORY	A	B	C	D
S-35	580-¾ 531 (600-¾)		580-1¼ 531 (600-1¼)	
C CIRCLING	600-1 551 (600-1)	700-1 651 (700-1)	1220-3 1171 (1200-3)	
DIKEY FIX MINIMUMS				
S-35	500-¾ 451 (500-¾)		500-1 451 (500-1)	
C CIRCLING	600-1 551 (600-1)	700-1 651 (700-1)	1220-3 1171 (1200-3)	



FAF to MAP 4.3 NM

Knots	60	90	120	150	180
Min:Sec	4:18	2:52	2:09	1:43	1:26

NE-1, 18 APR 2024 to 16 MAY 2024
NE-1, 18 APR 2024 to 16 MAY 2024