WAAS	APP CRS		
CH **78311**	**172°**	Rwy Idg	**5900**
W17A		TDZE	**248**
		Apt Elev	**250**

RNAV (GPS) RWY 17

CORVALLIS MUNI (CVO)

RNP APCH - GPS.

Circling Rwy 28 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, procedure NA. For inop ALS, increase LNAV Cat C/D visibility to 1¾ SM.

MALSR

MISSED APPROACH: Climb to 1100 then climbing left turn to 3700 direct INNOP and hold, continue climb-in-hold to 3700.

AWOS-3PT	CASCADE APP CON ★	UNICOM
135.775	**127.5 348.7**	**123.075** (CTAF) L





REIL Rwy 35 L
HIRL Rwys 17-35 L
MIRL Rwys 10-28 L



CATEGORY	A	B	C	D
LPV DA	448-½ 200 (200-½)			
LNAV/VNAV DA	571-½ 323 (400-½)			
LNAV MDA	880-½ 632 (700-½)		880-1⅜ 632 (700-1⅜)	
C CIRCLING	880-1 630 (700-1)		920-1¾ 670 (700-1¾)	1080-2¾ 830 (900-2¾)

NW-1, 18 APR 2024 to 16 MAY 2024
NW-1, 18 APR 2024 to 16 MAY 2024