ILS or LOC RWY 23

WEST VIRGINIA INTL YEAGER (CRW)

LOC/DME I-CRW	APP CRS	Rwy ldg	6215
110.3	235°	TDZE	931
Chan 40		Apt Elev	947

DME or RADAR required.

Autopilot coupled approach NA below 1700. Rwy 23 helicopter visibility reduction below RVR 4000 NA. Inop table does not apply to S-ILS 23. For inop ALS, increase S-LOC 23 Cat A/B visibility to RVR 5500, and Cat C/D to 2 SM.

ALSF-1

MISSED APPROACH: Climb to 1800 then climbing right turn to 3000 direct HVQ VOR/DME and hold.

ATIS	CHARLESTON APP CON	CHARLESTON TOWER	GND CON	CLNC DEL
127.6	124.1 269.125	125.7 257.8	121.8 348.6	118.55



CATEGORY	A	B	C	D
S-ILS 23	1181/40 250 (300-¾)			
S-LOC 23	1640/40 709 (700-¾)		1640-1⅝ 709 (700-1⅝)	

FAF to MAP 4.5 NM					
Knots	60	90	120	150	180
Min:Sec	4:30	3:00	2:15	1:48	1:30

NE-4, 18 APR 2024 to 16 MAY 2024
NE-4, 18 APR 2024 to 16 MAY 2024