RNAV (GPS) RWY 14

MANSFIELD LAHM RGNL (MFD)

WAAS	APP CRS	Rwy Idg	9001
CH 53426	143°	TDZE	1276
W14A		Apt Elev	1297

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 36°C (96°F). When local altimeter not received, use Marion altimeter setting and increase all DA 107 feet and all MDA 120 feet, and LPV all Cats visibility to 1 SM, LNAV/VNAV all Cats, and LNAV Cat C/D to 1⅜ SM. Increase Circling Cat C/D visibility ½ SM. VDP and Baro-VNAV NA when using Marion altimeter setting.

MISSED APPROACH: Climb to 3000 direct PIRCI and hold.

ATIS	CLEVELAND APP CON ★	MANSFIELD TOWER ★	GND CON	UNICOM
125.3	124.2 360.65	119.8 (CTAF) L 291.775	121.8 291.775	122.95





CATEGORY	A	B	C	D
LPV DA	1476-¾	200 (200-¾)		
LNAV/VNAV DA	1557-⅞	281 (300-⅞)		
LNAV MDA	1620-1	344 (400-1)		
C CIRCLING	1760-1	463 (500-1)	2000-2 703 (800-2)	2000-2¼ 703 (800-2¼)



HIRL Rwys 5-23 and 14-32 L
REIL Rwys 5 and 23 L

EC-2, 18 APR 2024 to 16 MAY 2024
EC-2, 18 APR 2024 to 16 MAY 2024