

WAAS CH 82633 W05A	APP CRS 054°	Rwy Idg 3601 TDZE 3199 Apt Elev 3204
--	------------------------	---

RNAV (GPS) RWY 5


RAPID CITY RGNL (RAP)

⚠


For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C (-5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Ellsworth AFB altimeter setting and increase all DA 25 feet and all MDA 40 feet. VDP and Baro-VNAV NA with Ellsworth AFB altimeter setting.

MISSED APPROACH: Climb to 5300 direct EWEBU and hold.

ASOS 118.525	ELLSWORTH APP CON ★ 119.5 259.1	RAPID CITY TOWER ★ 125.85 (CTAF) 0 257.8	GND CON 121.9	UNICOM 122.95
------------------------	---	--	-------------------------	-------------------------



ELEV 3204	D	TDZE 3199
------------------	----------	------------------



VEKCU		WODAV		XEPWY		RW05	
6600		5300		3920		3234	
GP 3.00°		054°		033°		071°	
TCH 34		4.1 NM		4.3 NM		1.4 NM	
CATEGORY		A		B		C	
LPV		DA		3449-1 250 (300-1)		NA	
LNAV/VNAV		DA		3449-1 250 (300-1)		NA	
LNAV		MDA		3500-1 301 (300-1)		NA	
CIRCLING		3660-1 456 (500-1)		3840-1 636 (700-1)		NA	