


LOC I-GPI 111.5	APP CRS 020°	Rwy Idg TDZE Apt Elev 9007 2966 2977
---------------------------	------------------------	--

ILS or LOC Rwy 2
GLACIER PARK INTL (GPI)

DME required. RNAV 1-GPS or RADAR required for procedure entry.			MALSR	MISSED APPROACH: Climb to 4100 then climbing left turn to 12000 on heading 190° and FCA VOR/DME R-238 to KILLY/15.7 DME and hold, continue climb-in-hold to 12000.
Inop table does not apply to S-LOC 2 Cats C/D.				
ATIS 132.625	SALT LAKE CENTER 127.075 244.875	GLACIER TOWER★ 124.55 (CTAF)	GND CON 121.6	UNICOM 122.95



7 NM Holding Pattern				
14000 ← 200° 9000 020° →				
GS 3.00° TCH 51				
6 NM 6.3 NM 4.3 NM 4.5 NM				
CATEGORY	A	B	C	D
S-ILS 2	3166-1/2 200 (200-1/2)			
S-LOC 2	4440-3/4 1474 (1500-3/4)	4440-1 1474 (1500-1)	4440-3	1474 (1500-3)
CIRCLING	4440-1 1/4 1463 (1500-1 1/4)	4440-1 1/2 1463 (1500-1 1/2)	4440-3	1463 (1500-3)
WALNU FIX MINIMUMS (DUAL VOR RECEIVERS REQUIRED)				
S-LOC 2	3520-1/2	554 (600-1/2)	3520-1 1/8	554 (600-1 1/8)
CIRCLING	3520-1 543 (600-1)	3580-1 603 (700-1)	3640-1 3/4 663 (700-3/4)	3760-2 1/2 783 (800-2 1/2)

ELEV 2977	TDZE 2966
REIL Rwy 20 MIRL Rwy 12-30 HIRL Rwy 2-20	
FAF to MAP 8.8 NM	
Knots	60 90 120 150 180
Min:Sec	8:48 5:52 4:24 3:31 2:56

NW-1, 18 APR 2024 to 16 MAY 2024

NW-1, 18 APR 2024 to 16 MAY 2024