RNAV (GPS) RWY 24

BOWERMAN (HQM)

WAAS	APP CRS	Rwy Idg	5000
CH 86902	241°	TDZE	16
W24A		Apt Elev	18

T A — For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -6°C (22°F) or above 43°C (109°F). When local altimeter setting not received, procedure NA. Circling NA northwest of Rwy 6-24. DME/DME RNP- 0.3 NA. For inoperative MALSR, increase LPV Cat C visibility to ⅞ mile and LNAV Cat C visibility to 2½ miles.

MALSR (A5)

MISSED APPROACH: Climb to 2600 direct ZUNAD and hold.

ASOS	SEATTLE CENTER	UNICOM
135.775	128.3 269.0	122.7 (CTAF) L



ELEV 18 | TDZE 16



REIL Rwy 6 L
HIRL Rwy 6-24 L



CATEGORY		A	B	C	D
LPV	DA	226-½ 210 (300-½)		286-½ 270 (300-½)	NA
LNAV/VNAV	DA	676-1½ 660 (700-1½)			NA
LNAV	MDA	800-½ 784 (800-½)	800-¾ 784 (800-¾)	800-1¾ 784 (800-1¾)	NA
CIRCLING		800-1 782 (800-1)	800-1¼ 782 (800-1¼)	800-2¼ 782 (800-2¼)	NA

NW-1, 18 APR 2024 to 16 MAY 2024