RNAV (GPS) RWY 28

MILLVILLE MUNI (MIV)

WAAS	APP CRS	Rwy Idg	6003
CH **42700**	**281°**	TDZE	**85**
W28A		Apt Elev	**85**

RNP APCH-GPS.

T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Atlantic City altimeter setting and increase all DA/MDA 60 feet; increase LNAV/VNAV all Cats, LNAV Cats C/D and Circling Cat C visibility ¼ mile. VDP and Baro-VNAV NA when using Atlantic City altimeter setting.

MISSED APPROACH: Climb to 2000 direct TIYDU and right turn on track 030° to RUPDE and right turn 077° track to VCN VOR/DME and hold.

ASOS	ATLANTIC CITY APP CON	UNICOM
119.6	**124.6 327.125**	**123.0** (CTAF) L



ELEV 85	TDZE 85



MIRL Rwys 10-28 and 14-32 L

2000	TIYDU	tr 030°	RUPDE	tr 077°	VCN

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/ TCH 29)



CATEGORY	A	B	C	D
LPV DA	344-1 259 (300-1)			
LNAV/VNAV DA	405-1 320 (400-1)			
LNAV MDA	640-1 555 (600-1)		640-1½ 555 (600-1½)	640-1¾ 555 (600-1¾)
CIRCLING	640-1 555 (600-1)		660-1½ 575 (600-1½)	660-2 575 (600-2)

NE-2, 18 APR 2024 to 16 MAY 2024
NE-2, 18 APR 2024 to 16 MAY 2024